



# ***GYMGuard® CARPET TILES***

## **— TECHNICAL SPECIFICATIONS —**

|                       |   |
|-----------------------|---|
| <b>TILE SIZE</b>      | 39-3/8" x 78-3/4" (1 meter x 2 meter)                               |
| <b>TILE WEIGHT</b>    | 91.4 oz/sq yd   |
| <b>BACKING</b>        | Polyolefin Plus backing   |
| <b>PILE THICKNESS</b> | 3 mm (0.12") or 6 mm (0.21") of<br>100% solution-dyed polypropylene |
| <b>INSTALLATION</b>   | Loose-Laid  |

### **SAFETY**

|                              | Test Method  | Requirement    | Results               |
|------------------------------|--------------|----------------|-----------------------|
| <b>Flammability</b>          | ASTM E662-03 | ≤ 450          | Pass                  |
| <b>Critical Radiant Flux</b> | ASTM E648-03 | (CRF) of ≥0.22 | Pass; Class II Rating |
| <b>Surface Flammability</b>  | ASTM D2859   |                | Pass                  |
| <b>Slip</b>                  | ASTM C1028   |                | Pass                  |

|                 |   |
|-----------------|---|
| <b>WARRANTY</b> | 3 years (against defects in fabric and manufacturing, prorated) |
|-----------------|---|

### **OPTIONAL TILE TRANSPORT CART**

|                       |                            |
|-----------------------|----------------------------|
| <b>SIZE:</b>          | 43" X 80"                  |
| <b>TILE CAPACITY:</b> | 70 (APPROXIMATELY 957 LBS) |