



FENCEMATE® WINDSCREEN

— WARRANTY —

MANUFACTURING DEFECTS

Windscreen products are warrantied completely against manufacturing defects. Such defects include, but are not limited to, uncoated or improperly coated fabric, improper stitching, faulty or improperly placed grommets, defective heat-sealing, or incorrect size. Manufacturing defects would be apparent before use or shortly after the cover is put in use, and must be delineated to manufacturer at that time. Digital pictures showing the defect are required. Manufacturing defect claims for windscreens with extended use may be denied.

Upon verification of the defect, manufacturer will either replace cover, repair to customer's satisfaction, or issue full or partial credit.

The manufacturer reserves the right to make the final judgment on the stated options.

Warranty applies under conditions of normal use, but does not apply to problems resulting from unreasonable use, poor installation, mishandling, negligence, improper installation or intentional damage. See installation instructions at coversports.com/windscreen-installation.

PRORATED WARRANTY	
Product Code	Warranty
VCM18x14 Classic Mesh	3 years
VCP18X18 ArmorMesh	5 years
PP85	4 years
PP100	4 years
GM90	4 years
VCP1800	4 years

ULTRA-VIOLET LIGHT BREAKDOWN

Windscreens are warrantied against fabric breakdown from ultraviolet (UV) sunlight. UV breakdown is evident through brittleness of fabric, greatly reduced tear strength, and, at times, delamination of coating from base fabric.

Upon verification of the defect, covers will be repaired, replaced, or a credit will be issued at the prorated value of the windscreen. The manufacturer reserves the right to make final judgment on the stated options.

Freight charges for replacement of cover are not included under warranty.

WIND DAMAGE

Damage to a windscreen resulting from ties breaking and the windscreen pulling free from the fence is not covered under warranty. Zip ties are intended to break in bad storms to prevent damage to the fence. Replacement zip ties must be installed immediately to prevent damage to the windscreen. Refer to the installation guide for more information. Grommets are placed at 18" intervals on windscreen panels, and it is strongly recommended that a standard wrap (50 lb. tensile strength) tie or cord be attached through every grommet to minimize wind damage. Refer to the Windscreen Installation Instructions provided with every windscreen order. Additional copies of the Windscreen Installation Instructions can be provided by calling 800-445-6680 or emailing us at sales@coversports.com.

Windscreens higher than 6' must have a lacing lip of grommets or a pipe hem at intervals of 6' or less, otherwise, the warranty is void.

Report windscreen defects to sales@coversports.com. Please include proof of purchase.